

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **62222708 A**

(43) Date of publication of application: **30.09.87**

(51) Int. Cl **H03H 7/24**

(21) Application number: **61064765**

(71) Applicant: **SANYUU KOGYO KK**

(22) Date of filing: **25.03.86**

(72) Inventor: **KURAOKA MASANORI**


(54) PROGRAMMABLE ATTENUATOR

(57) Abstract:

PURPOSE: To realize nearly accurately attenuation of 0dB by providing through- bypass contacts whose number is less than the total number of through-contacts and short-circuiting input/output terminals.

CONSTITUTION: The through-bypass circuit 7 is formed between the input and output terminal 1, 2, and through-bypass contacts 7a, 7b whose number is less than the total number (e.g., eight) of through-contacts 6a, 6b are provided in the circuit 7. The attenuation of 0dB is attained by energizing a relay coil in the drive circuit (not shown in figure) so as to turn on both the through- bypass contacts 7a, 7b and to turn off all the main contacts 5a, 5b and the through-contacts 6a, 6b in an attenuator unit 3. Thus, the loss in the bypass circuit 7 is reduced remarkably and the attenuation nearly equal to 0dB is attained.

COPYRIGHT: (C)1987,JPO&Japio



BEST AVAILABLE COPY